



▶ Zerust[®] ActivPowder[™] (LS)-10F

The Zerust[®]/Excor[®] ActivPowder[™](LS)-10F is a VCI (Volatile Corrosion Inhibitor) powder designed to protect metal surfaces in large voids from corrosion. This self-fogging powder combines VCI protection with a Flash Corrosion Inhibitor (FCI[™]) to protect against flash rust and provide long-term corrosion protection.

Zerust/Excor ActivPowder(LS)-10F is a powerful ferrous corrosion inhibitor powder for challenging applications. The exceptionally fast diffusion rate of Zerust Activ[™] inhibitors enables rapid delivery of protection, even in hard to reach spaces of structural voids, tubing and cavities. It also provides effective surface passivation to protect lightly contaminated metal surfaces from corrosion. Add ActivPowder(LS) to voids to protect from corrosion after hydrostatic testing.

Apply powder by sprinkling or fogging into void spaces. To apply by spray, use a solution of powder dissolved in deionized water. Then, tightly seal the void or enclosure. At the end of its service life, ActivPowder(LS)-10F powder may be removed or it may remain in the enclosure. The powder is water soluble and should be added to any standing water that cannot be removed in the enclosure. The ActivPowder(LS) powder is a low odor and nitrite-free formula and has a REACH compliant Safety Data Sheet (SDS) available.

Application Example

Protect hard to reach spaces with rapidly diffusing ActivPowder(LS). It quickly reaches surfaces of internal spaces via its auto-fogging properties such as the inside of heat exchangers.



▶ Benefits

Fast acting and effective on hard to reach surfaces

Safe* and easy to use

Protects against flash corrosion

Does not cause hydrogen embrittlement

Protects against acid gases, salt air and other challenging contaminants

Powerful and long-lasting protection

Application Type

Storage
Shipping
During Operation
May be used with Zerust Packaging

*Safe to use and handle. Product is not hazardous for people or the environment according to EU (CLP) or OSHA HazCom 2012 (US GHS).



Protect large void spaces of metals assets in storage and lay-up

Specifications

Product Information Zerust®/Excor® ActivPowder(LS)-10F is a VCI (Vapor Corrosion Inhibitor) and FCI (Flash Corrosion Inhibitor) white powder.

Protected Metal Types Ferrous protection. Multimetal compatible. Do not place in direct contact with copper, brass or zinc. Test before use.

Properties

pH	9 - 10.5
Solubility	> 25 g/L

Storage Store tightly closed in original container in a cool, dry place and away from sunlight for up to 2 years. Store at or below 40% RH.

Availability

Zerust/Excor ActivPowder(LS)-10F is stocked in pails. A 5-7 day lead time may apply. Call to confirm. Additional quantities such as super sacks available upon request.

ActivPowder(LS)	Quantity
460-F-00003	30 lb (14 kg)

Protection Capabilities*

Zerust® Product Name	Normal Environment**		Aggressive Environment**	
	Volume of Protection	Duration of Protection (Up To)	Volume of Protection	Duration of Protection (Up To)
ActivTab™(LS)-25	0.25 ft³ (0.0071 m³)	6 months	0.025 ft³ (0.0007 m³)	15 days
ActivCapsule™ FAC1-1s	4 ft³ (0.12 m³)	1 year	0.35 ft³ (0.01 m³)	1 month
ActivPak'(LS)-35	35 ft³ (1 m³)	1 year	11 ft³ (0.3 m³)	2 months
ActivPak-35	35 ft³ (1 m³)	2 years	11 ft³ (0.3 m³)	4 months
ActivPowder™(LS)-10F	1 lb = 280 ft³ (8 m³)	3 years	1 lb = 90 ft³ (3 m³)	1 year
ActivPowder-10F	1 lb = 280 ft³ (8 m³)	3-15 years	1 lb = 90 ft³ (3 m³)	1-5 years

* Protection ratings are based on the highest average tested protection properties and are not guaranteed. Results may vary according to usage environment and metal surface properties such as contaminants.

** Normal environment (below 0.2 ppm SO₂) defined as warehouses, light industrial areas, and shipping and storage in sealed packaging or enclosures. Aggressive environment (at or above 0.2 ppm SO₂) defined as areas located in the vicinity of salts and acid gases such as oceans, petrochemical sites, wastewater treatment and pulp-paper plants or in enclosures that are not well sealed.

Warranty and Disclaimer Information: We guarantee our products conform to documented quality specifications. All statement, technical information and recommendations contained herein are based on testing and experiences NTIC believes to be reliable, but the accuracy or completeness thereof is not guaranteed. Product information subject to change without notice. We make no warranty of any kind expressed or implied as to the effects of use (including, but not limited to, damage or injury). For full warranty and disclaimer information visit, www.zerust.com/warranty.

©2013-2017 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor-Tab®, EXCOR®, Flange Saver®, ICT®, NTI®, Plastabs®, Z-CIS®, Zerion®, ZERUST®, The ZERUST People®, and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

Safety

- Safe to use and handle. Product is not hazardous for people or the environment according to EU (CLP) or OSHA HazCom 2012 (US GHS).
- Product in unopened original container prior to use does not meet criteria for hazardous waste according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).

Contact Us



A product of:
Northern Technologies
International Corp
4201 Woodland Road
Circle Pines, MN 55014
USA

Phone. +1 763.225.6600
Fax. +1 763.225.6645
sales@zerust.com
www.zerust.com